

FormMail.pl on NetWare Quick Reference

John Henry Maurice
December 7, 2003

1. Download FormMail from <http://nms-cgi.sourceforge.net/scripts.shtml>.

2. Extract all file to a temporary directory. The following files will be extracted:

```
formmail_modules-3.09m1/FormMail.pl
formmail_modules-3.09m1/README
formmail_modules-3.09m1/EXAMPLES
formmail_modules-3.09m1/ChangeLog
formmail_modules-3.09m1/MANIFEST
formmail_modules-3.09m1/lib/CGI/NMS/Charset.pm
formmail_modules-3.09m1/lib/CGI/NMS/Validator.pm
formmail_modules-3.09m1/lib/CGI/NMS/Script.pm
formmail_modules-3.09m1/lib/CGI/NMS/Script/FormMail.pm
formmail_modules-3.09m1/lib/CGI/NMS/Mailer.pm
formmail_modules-3.09m1/lib/CGI/NMS/Mailer/ByScheme.pm
formmail_modules-3.09m1/lib/CGI/NMS/Mailer/Sendmail.pm
formmail_modules-3.09m1/lib/CGI/NMS/Mailer/SMTP.pm
```

3. Place FormMail.pl in you cgi directory - SYS:/Perl/web.
4. Place the library files in SYS:/Perl/lib/CGI.
5. Edit FormMail.pl to meet your needs as per the README file.
6. Edit SYS:/Perl/lib/CGI/NMS/Script.pm as follows:

Replace:

```
$ENV{PATH} =~ /(.*)/m or die;
local $ENV{PATH} = $1;
local $ENV{ENV} = '';
```

With:

```
{
  no warnings 'uninitialized';
  $ENV{PATH} =~ /(.*)/m or die;
  local $ENV{PATH} = $1;
  local $ENV{ENV} = '';
}
```

This will prevent the following perl warning being generated.

```
"Use of uninitialized value in pattern match (m//) at
sys:\perl\lib\CGI\NMS\Script.pm line 193."
```